

Vital 124

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Natural latex
- **Length (cm)** 30.5
- **Thickness (mm)** 0.35
- **Wrist** Straight cuff
- **Colour/Color** Yellow
- **Interior finish** Flocked
- **Exterior finish** Embossed texture
- **Size / EAN** 6 7 8 9 10
- **Packaging** 1 pair/bag - 10 pairs/bag - 100 pairs/carton



PERFORMANCE RESULTS

Certification category 3

CE 0334



Dexterity EN 420 : 5/5

KPT

0010X

Legends

ANSI	CUT RESISTANCE		
A1	A1 ≥ 200 G	A4 ≥ 1500 G	A7 ≥ 4000 G
	A2 ≥ 500 G	A5 ≥ 2200 G	A8 ≥ 5000 G
CUT	A3 ≥ 1000 G	A6 ≥ 3000 G	A9 ≥ 6000 G

EN 511	COLD HAZARDS		
	PERFORMANCE LEVELS		
	0-4	0-4	0 or 1
		Water permeability	Contact cold resistance
		Convective cold resistance	

EN 407	THERMAL RISKS		
	Heat and fire		
	PERFORMANCE LEVELS		
	0-4	0-4	0-4 0-4 0-4 0-4
		Resistance to large quantities of molten metal	Resistance to small drops of molten metal
		Radiant heat resistant	Convective heat resistance
		Contact heat resistance	Burning behaviour

PROTECTION FROM PESTICIDES

ISO 18889	ISO 18889	ISO 18889
G1	G2	GR

MICRO-ORGANISMS

EN ISO 374-5	EN ISO 374-5
Protection against bacteria, fungi	Protection against bacteria, fungi, virus
	VIRUS

CHEMICAL RISKS

EN ISO 374-1	EN ISO 374-1	EN ISO 374-1
Type A	Type B	Type C
U V W X Y Z	X Y Z	
A Methanol	J n-Heptane	
B Acetone	K Sodium hydroxide 40%	
C Acetonitrile	L Sulphuric acid 96%	
D Dichloromethane	M Nitric acid 65%	
E Carbon Disulfide	N Acetic acid 99%	
F Toluene	O Ammonia 25%	
G Diethylamine	P Hydrogen peroxide 30%	
H Tetrahydrofurane	S Hydrofluoric acid 40%	
I Ethyl acetate	T Formaldehyde 37%	

EN 388 MECHANICAL HAZARDS

EN 388	MECHANICAL HAZARDS		
	PERFORMANCE LEVELS		
	0-4	0-5	0-4 0-4 A-F (P)
		Resistance to large quantities of molten metal	Resistance to small drops of molten metal
		Radiant heat resistant	Convective heat resistance
		Contact heat resistance	Burning behaviour
		Impact protection	Cut resistance according to ISO 13997
		Puncture resistance	Tear resistance
		Blade cut resistance	Abrasion resistance

RADIOACTIVE CONTAMINATION



ELECTROSTATIC DISCHARGE PROTECTION



For more details: www.mapa-pro.com

MAPA[®]
PROFESSIONAL

SPECIFIC ADVANTAGES

- Excellent dexterity from the suppleness of natural latex
- Good resistance
- Comfortable cotton flock-lining

MAIN FIELDS OF USE

Mechanical industry

- Assembly of small, oil and grease free parts

Food industry

- Common cleaning Tasks

Local Authorities (Cleaning)

- Handling household detergents

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- It is not recommended for persons sensitised to natural latex, dithiocarbamates and thiazoles to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

- Store the gloves in their original packaging protected from direct sunlight, far from heat sources or electric equipment.

Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in contact with a solvent (alcohol, etc...) : rub over with a dry cloth.
- in contact with acids or alkalies: thoroughly rinse the gloves under running water, and rub over with a dry cloth.
- Caution : improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

Drying conditions

- Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0075/014/162/03/18/0525
- **Issued by the notified body nr** : 0075 - C.T.C – 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
- **Quality assurance certificat** : 0334 Asqual 14 rue des Reculettes -F-75013 PARIS