



PRODUCT NUMBER: 1822120

X-PRO

X-Pro with SX-Pro demand valve and Opti-Pro full-face mask with five-point straps.

Honeywell

Overview

Reference Number

1822120

Product Type

Respiratory Protection

Range

SCBA (Self Contained Breathing Apparatus)

Brand

Honeywell

Brand formerly known as

FENZY

Industry

- Chemical Industries
- Fire Protection brigades
- Petro-chemical

Product Use

Its construction integrates many passive safety elements and modular function, offering an optimal protection for the user in every kind of environments and extreme applications. Approved to -30 to +60°C.

Features & Benefits

Feature

Ultra-light, height adjustable back plate for various body shapes

Benefit

Improved comfort

Feature

Thermo-compressed fibre comfort cushions on the shoulders, waist belt straps and on the upper back straps

Benefit

Improved comfort

Feature

Curved shoulder straps, specially designed to maintain the apparatus on the shoulders, regardless of the user's position or movements

Benefit

Improved comfort

Feature

Rotating hip belt

Benefit

Improved comfort

Feature

Sx-Pro quick click first breath activated positive pressure, compensated demand valve

Benefit

Improved comfort and simplicity of use

Feature

Limited maintenance

Benefit

Life cycle cost reduced

Feature

For increased protection, the high- and medium pressure hoses are integrated into the back plate, reducing risk of damage

Benefit

Increased safety

Feature

Movable and foldable foot protecting the cylinder and the high-pressure system from impacts

Benefit

Increased safety

Technical Description

SCBA

Standard

EN137, SOLAS, MED, MSCAS, ATEX

Face Pieces

OPTI-PRO

Head Harness

5-point head harness

Head Harness Material

Silicone

Head Harness Color

Black

Skirt

3 sizes

Skirt Material

Silicone

Skirt Size

Standard

Nose Cup Material

Silicone

Nose Cup Color

Black

Nose Cup Size

Standard

Lens

Panoramic

Lens Material

Polycarbonate

Backpack Harness

Approx 3,9 kg (complete without cylinder)

Stage 2 Regulator

Approx 3,9 kg (complete without cylinder)

Low Air Audible Alarm

Plain Whistle

Pressure Gauge

0-400 bars, photo-luminescent, rubber protection and integrated alarm whistle

Visual Alarm

Optionnal

Cylinder

Steel or composite

Certifications

 E.C. Declaration of Conformity

EC Category PPE

3

EC Certificate Number

0082/236/079/12/14/0466

EC Attestation

 CE Certificate Fenzy X-Pro

EC Attestation Number

0082/236/079/12/14/0466

Certifications

- EN 136
- EN 137

Additional Information

User Manual

User Manual Fenzy X-Pro