



ppbRAE 3000

Portable Handheld VOC Monitor



The compact ppbRAE 3000 is a comprehensive VOC gas monitor and datalogger for hazardous environments. The ppbRAE 3000 is the most advanced handheld VOC monitor available for parts-per-billion detection. This third-generation patented PID device monitors VOCs using a photoionization detector with a 9.8 eV, 10.6 eV UV-discharge lamp.

The built-in wireless modem allows real-time data connectivity with the ProRAE Guardian command center located up to two miles/3 km away (with optional RAElink3 portable modem) from the ppbRAE 3000 detector.

- Accurate VOC measurement in all operating conditions
- Easy access to lamp and sensor in seconds without tools
- Patented sensor and lamp auto-cleaning reduces maintenance
- Monitors real-time readings and location of people
- Low Cost of Ownership: 3-year 10.6 eV lamp Warranty

KEY FEATURES

Proven PID Technology

- 3-second response time
- Extended range from 1 ppb to 10,000 ppm with best in class linearity
- Humidity compensation with integral humidity and temperature sensors

Integrated

- Real-time wireless built-in – Bluetooth (and optional RAElink3 portable modem) or Mesh Network support
- Integrated Correction Factors list of 220 compounds—more than any other PID
- Includes flashlight for dark conditions
- Large graphic display presents gas type, Correction Factor and concentration

Durable

- Easy access to battery, lamp and sensor in seconds without tools
- Rugged housing withstands use in harsh environments
- IP-67 waterproof design for easy cleaning and decontamination

APPLICATIONS

- Oil & Gas
- HazMat
- Industrial Safety
- Civil Defense
- Environmental & Indoor Air Quality



Workers can easily measure VOCs and wirelessly transmit readings up to two miles/3 km away.



ppbRAE 3000

Portable Handheld VOC Monitor



Specifications

Detector Specifications

Size	10" L x 3.0" W x 2.5" H (25.5 cm x 7.6 cm x 6.4 cm)
Weight	26 oz (738 g)
Sensors	Photoionization sensor with standard 10.6 eV or optional 9.8 eV lamp
Battery	<ul style="list-style-type: none">Rechargeable, external field-replaceable Lithium-Ion battery packAlkaline battery adapter
Operating Hours	16 hours of operation (12 hours with alkaline battery)
Display Graphic	4 lines, 28 x 43 mm, with LED backlight for enhanced display readability
Keypad	1 operation and 2 programming keys, 1 flashlight on/off
Direct Readout	Instantaneous reading <ul style="list-style-type: none">VOCs as ppm by volume or mg/m³ (3 in upper case for cubic)STEL, TWA and PEAKBattery and shutdown voltageDate, time, temperature
Alarms	95 dB (at 12"/30 cm) buzzer and flashing red LED to indicate exceeded preset limits <ul style="list-style-type: none">High: 3 beeps and flashes per secondLow: 2 beeps and flashes per secondSTEL and TWA: 1 beep and flash per secondAlarms latching with manual override or automatic resetAdditional alarm for low battery and pump stall
EMI/RFI	Highly resistant to EMI/RFI Compliant with EMC Directive 89/336/EEC
IP Rating	<ul style="list-style-type: none">IP-67 unit off and without flexible probeIP-65 unit running
Datalogging	Standard 6 months at one-minute intervals
Calibration	Two-point or three-point calibration for zero and span Calibration memory for 8 calibration gases
Sampling Pump	<ul style="list-style-type: none">Internal, integrated flow rate at 500 cc/mnSample from 100' (30m) horizontally and vertically
Low Flow Alarm	<ul style="list-style-type: none">Auto pump shutoff at low-flow condition
Communication & Data Download	<ul style="list-style-type: none">Download data and upload instrument set-up from PC through charging cradle or optional Bluetooth™Wireless data transmission through built-in RF modem
Wireless Network	Mesh RAE Systems Dedicated Wireless Network
Wireless Range (Typical)	EchoView Host: LOS > 660 ft (200 m) ProRAE Guardian & RAEMesh Reader: LOS > 660 ft (200 m) ProRAE Guardian & RAELink3 Mesh: LOS > 330 ft (100 m)
Safety Certifications	<ul style="list-style-type: none">US and Canada: UL, cUL, Classified as Intrinsically Safe for use in Class I, Division 1 Groups A, B, C, DEurope: ATEX Ex II 2GEx ia IIC/IIB T4IECEX: Ex ia IIC/IIB T4
Temperature	-4° to 113° F (-20° to 50° C)
Humidity	0% to 95% relative humidity (non-condensing)
Attachments	Durable black rubber boot with straps
Warranty	3-year warranty for 10.6 eV lamp, 1 year for pump, battery, and instrument
Wireless Frequency	ISM license-free band. IEEE 802.15.4 Sub 1GHz
Wireless Approvals	FCC Part 15, CE R&TTE, Others ¹
Radio Module	Supports Bluetooth or RM900

¹ Contact RAE Systems for country-specific wireless approvals and certificates.

Specifications are subject to change.

CORPORATE HEADQUARTERS

RAE Systems by Honeywell
3775 North First Street
San Jose, CA 95134 USA
RAE-InsideSales@honeywell.com

WORLDWIDE SALES OFFICES

USA/Canada 1.877.723.2878
Europe +800.333.222.44/+41.44.943.4380
Middle East +971.4.450.5852
China +86.10.5885.8788-3000
Asia Pacific +852.2669.0828

Sensor Specifications

Gas Monitor	Range	Resolution	Response Time T90
VOCs	0 to 9999 ppb	1 ppb	< 3 s
	10 to 99 ppm	0.01 ppm	< 3 s
	100 to 999 ppm	0.1 ppm	< 3 s
	1000 to 9999 ppm	1 ppm	< 3 s

Monitor only includes:

- ppbRAE 3000 Monitor, with RAE Systems UV lamp, as specified
- Datalogging with ProRAE Studio II
- Charging/download adapter
- VOC Zeroing Tubes (1 box)
- Tube adapter
- Tedlar® bag for calibration
- Flex-I-Probe™
- External filter
- Rubber boot with straps
- Alkaline battery adapter
- Lamp-cleaning and tool kit
- Operation CDROM
- Operation & Maintenance manual
- Soft leather case

Monitor with accessories kit adds:

- Hard transport case with pre-cut foam padding
- Charging/download cradle
- 5 Porous metal filters and O-rings
- Organic vapor zeroing kit
- Gas outlet port adapter and tubing

Optional calibration kit adds:

- 10 ppm isobutylene calibration gas, 34L
- Calibration regulator and flow controller

Optional Guaranteed Cost of Ownership Program:

- 4-year repair and replacement guarantee
- Annual maintenance service