Harpon 321

DESCRIPTION AND GENERAL PROPERTIES

- Material Natural latex
- Length (cm) 32
- Thickness (mm) 1.35
- Wrist Scalloped cuff
- Colour/Color Orange
- Interior finish Textile support
- Exterior finish Reinforced grip
- Size / EAN 6 7 8 9 10
- Packaging 1 pair/bag 50 pairs/carton
- Complementary information Guaranteed without silicone Lightly powdered surface



PERFORMANCE RESULTS

Certification category 3



CUT

EN 407







Dexterity EN 420:5/5

EN 511 COLD HAZARDS

PERFORMANCE LEVELS

0-4 0-4 0 or 1

THERMAL RISKS

Heat and fire

PERFORMANCE LEVELS

Burning behaviour

0-4 0-4 0-4 0-4 0-4

Contact heat resistance



A1 ≥ 200 G $\pmb{\mathsf{A4}}\ \geq 1500\ G$ $\textbf{A7} \ \geq 4000 \ G$ **A2** ≥ 500 G $\textbf{A5} \ \geq 2200 \ G$ **A8** ≥ 5000 G **A3** $\geq 1000 \text{ G}$ $\textbf{A9} \ \geq 6000 \ G$

└ Water permeability

Contact cold resistance

- Radiant heat resistant

Convective heat resistance

Convective cold resistance

ISO 18889

UVWXYZ

EN ISO 374-1

Type A

Methanol Acetone C Acetonitrile

Dichloromethane Carbon Disulfide

Toluene G Diethylamine

Tetrahydrofurane н Ethyl acetate

RADIOACTIVE CONTAMINATION



Type B

n-Heptane

CHEMICAL RISKS EN ISO 374-1

X Y 7

Type C

EN ISO 374-1

Sodium hydroxide 40% Sulphuric acid 96%

Nitric acid 65% Acetic acid 99%

Ammonia 25%

Hydrogen peroxide 30% Hydrofluoric acid 40%

Formaldehyde 37%

ELECTROSTATIC DISCHARGE PROTECTION EN 16350



MICRO-ORGANISMS




Protection against bacteria, fungi



Protection against bacteria, fungi, virus

EN 388 MECHANICAL HAZARDS



For more details: www.mapa-pro.com



L Resistance to large quantities of molten metal

Resistance to small drops of molten metal

SPECIFIC ADVANTAGES

- Suitable for long-term wear, due to the comfort of a textile support and good thermal insulation
- Optimised service life: high resistance to abrasion

MAIN FIELDS OF USE

Fishing

- · Fish-handling
- · Oyster farming
- Work with frozen products

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at the workplace may differ from the "CE"-type tests.
- It is not recommended for persons sensitized to natural latex, dithiocarbamates and thiazoles to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service MAPA PROFESSIONAL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.

Storage conditions

• Store the gloves in their original packaging protected from direct sunlight, far from heat sources or electric equipment.

Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in use with a solvent (alcohol, etc...) : rub over with a dry cloth
- in use with detergents, acids or alkalies: thoroughly rinse the gloves under running water, and rub over with a dry cloth
- Caution: improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

Drying conditions

• Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) $n^21272/2008$ of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation $n^2 1907/2006$ of the European Parliament and of the Council (REACH).

- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0245
- \bullet Issued by the notified body nr: 0075 CTC. -4 rue Hermann Frenkel F-69367 LYON CEDEX 07

