



PRODUCT NUMBER: 1765059
Airvisor 2 DAC chemical kit

Full kit : AIRVISOR 2 DAC with acetate chemical resistant visor, 2 disposable visor covers, fabric hood and neck cover, waistbelt complete with double action connector, carry bag. For applications exposed to chemicals.

Honeywell

Overview

Reference Number

1765059

Product Type

Respiratory Protection

Range

Supplied Air Respirators

Line

Loose fitting visors

Brand

Honeywell

Brand formerly known as

WILLSON

Industry

- Automotive and Part Manufacturer
- Aviation
- Chemical Industries
- Industrial Cleaning
- Iron and steel industry
- Laboratory
- Medical and Pharmaceutical
- Metal steel
- Ship Building
- Utilities
- Wood Industries

Product Use

For use in the general chemical industry where the respirator is intended for use without any auxillary air tool or spraygun connected to it.

Features & Benefits

Feature

Lightweight product

Benefit

Comfort and pleasure in use

Feature

Double action connector

Benefit

Supplementary connection safety in severe conditions

Feature

Wild field of vision

Benefit

Limited falls and trips

Feature

Single use head and neck protection

Benefit

Hygienic

Feature

Visor keeps its original appearance due to visor cover

Benefit

Clarity and better field of vision

Feature

Carbon filter element

Benefit

Removes odors

Technical Description

Mask

Headpiece

Visor

Material

Main shell components - Polypropylene Face Seal - Non-woven polypropylene

Visor Screen

Chemical resistant

Visor Screen Material

Cellulose acetate

Visor Screen Covers

Polyester (anti-static coating)

Head and Neck Cover

Non-woven polypropylene

Air Diffuser

Silencer (open cell foam in rigid casing)

Belt

Belt or Harness

Waistbelt

Material

Woven Polyester

Hose

Hose

Food grade PVC material, complete with High Flow Quick Release connectors

Length Hose

Selection from 3.5m to 10m

Compressed Airline Infiltration System

Wall Model

Selection from range (Clearflow 3)

Floor Model

Selection from range (Clearflow 3)

Supply Pressure

4,2 (58 psi) to 7 bars (102 psi)

Airflow Rate

290 l/min

Certifications

 E.C. Declaration of Conformity

EC Category PPE

3

EC Certificate Number

2582

EC Attestation

 CE Certificate Airvisor 2

EC Attestation Number

2582

Certifications

- EN 14594

Additional Information

User Manual

Airvisor 2 user manual - Multi languages

Packaging

Quantity per Box/Pack/Case

1

Quantity per Carton

1

Quantity for Minimum Order

1